



VERIFICATION OF COMPLIANCE

No.: GZES2303003728PVA01

Applicant: EcoFlow Inc.
Plant A202, Founder Technology Industrial Park, Shiyan
Subdistrict, Bao'an District Shenzhen, 518000 Guangdong
China.

Manufacturer: EcoFlow Inc.
Plant A202, Founder Technology Industrial Park, Shiyan
Subdistrict, Bao'an District Shenzhen, 518000 Guangdong
China.

Product Name: EcoFlow PowerStream Microinverter

Product Description: Inverter used in PV system

Model No.: EFWN511, EFWN511B

Trade Mark: 

Rating: Refer to page 2

Protection against Electric Shock: Class I

Additional Information (if any): IP 67
Software Version: V1.0

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: ENA Engineering Recommendation G98 Issue 1 Amendment 7
2022

as shown in the

Test Report Number(s): GZES230300372802

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.

David Guo
Senior Technical Manager

2023-06-30

SGS-CSTC

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>
Member of SGS Group (Société Générale de Surveillance)



No.:

GZES2303003728PVA01

Other information added:

Rating:

Model	EFWN511	EFWN511B
PV Input		
Max. input voltage	55 Vdc	
MPPT operating voltage range	11-55 Vdc	
Max. input current	13 A/13 A	
Battery Input		
Battery charge voltage range	30V-58 Vdc	
Battery charge current	13 A	
Battery discharge voltage range	11V-15, 40-59 Vdc	
Battery discharge current	13 A	
AC Output		
Nominal grid voltage	L/N/PE, 230Vac	
Nominal grid frequency	50 Hz	
Rated AC power	800 W	600 W
Max. AC apparent power	800 VA	600 VA
Rated AC current	3.5 A	2.6A
Max. AC current	3.7 A	2.8A
Output power factor	1 default (adjustable+/-0.8)	
General Data		
Operating temperature range	-40 °C ~ +50 °C	
Protection degree	IP67	
Protective class	Class I	
Cooling method	Natural Cooling	
Topology	Isolated	

David Guo

Senior Technical Manager

SGS-CSTC

2023-06-30

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>

Member of SGS Group (Société Générale de Surveillance)